



Wine-Mate 2520SSL

Split Low-Profile Wine Cooling System

Key Features

- Stable temperature between 50~65 °F
- Maintain humidity of 50~75% RH even when the environment becomes dry or humid
- The condensing unit can be placed away from the wine room as far as 75 feet, which will bring an extremely quiet operation
- Perfect for storing cigars, chocolate, salami, and fine leather and furs (additional cost and customization required)

Specifications

Cellar Size:	230 cu ft
Btu/h, CFM:	2100 Btu/h, 230 CFM
Decibel Rating:	47 dBA
Dimensions:	Evaporator: 31-3/4"W x 14-1/2"D x 4-3/4"H Condenser: 18"W x 14"D x 12"H
Electrical:	Evaporator: 220V/50Hz/0.2A Condenser: 220V/50Hz/3A
Weight:	Evaporator: 20 lbs Condenser: 40 lbs
Refrigerant:	R134a
Thermostat:	Advanced Digital Control Display

Features

Wine-Mate ceiling mount split cooling systems WM-2520~6520SSL are designed and used to provide a cold temperature between 50~65 °F for a properly insulated wine cellar. The wine cellar will maintain humidity range within 50~75% RH. These temperature and humidity ranges like in natural caves are optimized for long term storage of wine. SSL units consist of a condensing unit and an evaporator unit; they are connected by a liquid line and an insulated suction line. SSL condensing units can be located away from the wine cellars 75 ft so that noise and compressor vibration are isolated. SSL evaporator units provide low profile and whisper quiet operation. The evaporator units can be installed on the ceiling in a small cabinet or room. This item is for non-domestic use only.